## **Product fiche**

Delegated Regulation (EU) 626/2011

Supplier name or trademark	NØRDIS / NORDIS
Model identifier	ORION PRO NDI/NDO-OP09TC1
Indoor Model Identifier(s)	NDI-OP09TC1
Outdoor Model Identifier	NDO-OP09TC1
Inside sound power levels (Cooling mode)	54 dB
Inside sound power levels (Heating mode)	54 dB
Outside sound power levels (Cooling mode)	62 dB
Outside sound power levels (Heating mode)	62 dB
Refrigerant Name	R32
Refrigerant GWP	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO 2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

r		
Cooling Mode		
Seasonal Energy Efficiency Ratio (SEER)	6,2	
Energy Efficiency Class	A++	
Annual Electricity Consumption	Energy consumption 152 kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.	
Design Load	2,7 kW	
Heating Mode		
Seasonal Coefficient Of Performance (SCOP) (Average season)	4,0	
Energy Efficiency Class (Average season)	A+	
Annual Electricity Consumption (Average season)	Energy consumption 840 kWh per year, based on stan- dard test results. Actual energy consumption will depend on how the appliance is used and where it is located.	
Seasonal Coefficient Of Performance (SCOP) (Warmer season)	5,1	
Seasonal Coefficient Of Performance (SCOP) (Colder season)	3,4	
Energy Efficiency Class (Warmer season)	A+++	
Energy Efficiency Class (Colder season)	A	
Annual Electricity Consumption (Warmer season)	714 kWh/annum	
Annual Electricity Consumption (Colder season)	1 606 kWh/annum	
Design Load (Average season)	2,4 kW	
Design Load (Warmer season)	2,6 kW	
Design Load (Colder season)	2,6 kW	
Declared capacity (Average season)	2,2 kW	

Declared capacity (Warmer season)	2,6 kW
Declared capacity (Colder season)	2,2 kW
Backup heating capacity (Average season)	0,2 kW
Backup heating capacity (Warmer season)	0,0 kW
Backup heating capacity (Colder season)	0,4 kW